

Your 'Hero to Zero Emissions'





RANGE 225.3 KILOMETERS



BATTERY SIZE 194 KWH

CHARGE TIME AND POWER REQUIREMENT STANDARD SINGLE PHASE, 208-240 VOLT, 80 AMP, 19.2KW 10.5 HOURS

DC FAST CHARGE THREE PHASE, 575 VOLT, 100 AMPS, 60KW 3.25 HRS

PASSENGER CAPACITY 90 SEATED ADA



THE BEAST GIVES YOU MORE ...

SCHO

USA 909-308-0960 CANADA 604-563-4144 GREENPOWERMOTOR.COM

TECHNICAL DATA

CLASSIFICATION

<u>Heavy-duty class 8, Type D</u>

GVWR

<u>19,500 kg</u>.

PAYLOAD CAPACITY * 13,790 lbs.

AXLE WEIGHT LOAD RATING Front: 6,500 kg., Rear: 11,000 kg.

LENGTH 3

12.2 meters.

WHEELBASE 4

609 cm

OVERHANG 5 265 cm (front), 324 cm (rear)

APPROACH & DEPARTURE ANGLES 6

8 (front), 8 degrees (rear)

WIDTH (2) 259 cm, widest in the industry

HEIGHT * (1)

352 cm **TIRES**

<u>295 / 80R / 22.5 (qty. 6)</u>

TURNING RADIUS 12.6 meters (outside body)

SUSPENSION Air ride suspension

PASSENGER DOOR Electric, 91 cm wide, 86 cm opening

EMERGENCY EXITS Hatch, window, door

natch, window, d

ADA Yes

HVAC 75,000 BTU/h, front, rear, electric

ECU COMMUNICATION CAN BUS, J1939

CHP CERTIFIED



BUY AMERICA *

SEATING CONFIGURATION * 7 Front facing bench seating, 15 rows, 2 benches per row, 3 seats per bench

MAX SEATING CAPACITY (w/driver) 91 seating

STORAGE

Full pass-through storage compartment

BATTERY CAPACITY 193.5 kWh, 6 total packs

RANGE * 225.3 kilometers

FUEL ECONOMY * 9.7 kple, 0.93 kWh/km, 1.07 km/kWh

TOP SPEED 109.4 kph

MOTOR POWER

<u>350 kW max</u>

TRANSMISSION Direct drive, No transmission

BRAKES Full ABS disc brakes

FRAME / BODY / ROOF Steel, monocoque

DESIGN LIFE

10 years

LCFS EER VALUE * HDV, 5.0 EER, 1 credit every 740 kWh

CHARGING* CCS1,

LV2 AC 19.2kW, 10.5 hours. 60kW DCFC, 3.25 hours.

VOUCHER INCENTIVES

For additional grant assistance, Please call (604) 563-4144 or email sales@greenpowermotor.com

 Specification can vary by region, application, availability









